



VidyoPortal™

VidyoConferencing™ Management



VidyoPortal™ is an essential component of the VidyoConferencing™ infrastructure with enterprise-class management tools accessible through an intuitive, browser-based interface and the capacity to support tens of thousands of users. Administrators will appreciate its flexibility and control while end users will find it easy to manage their own virtual conference space. Administrators can configure and manage endpoints, infrastructure, software, and licenses, and moderate conferences in progress. VidyoPortal also provides individualized multi-tenant support on a single physical device, and the ability to configure tenant and global settings, with options to make each tenant appear as a private portal or to enable visibility and conferencing between specific tenants. VidyoPortal offers all this in a 1U form factor.

Key Features

Flexible Provisioning

- Create user accounts, groups, and bandwidth policies
- Create and manage personal and public reservation-less meeting rooms
- Populate global Address Books with Vidyo and legacy (H.323 and SIP) endpoints
- Configure LDAP/Active Directory integration
- Assign user groups and tenants to VidyoRouter™ pools to optimize bandwidth usage and network delays
- Tenant administrators can add, delete and manage users, set up public rooms and groups, and define maximum participants and bandwidth for their users

Optional Licenses and Extensions

- VidyoPortal Hot Standby License
- Secure VidyoConferencing License
- VidyoPortal Multi-tenant License
- Plug-ins for Microsoft Outlook® and Microsoft Lync®, IBM Sametime®, and Adobe® Connect™

Ease of Maintenance

- Automatically distribute software to VidyoDesktop™, VidyoRoom™, and VidyoPanorama™ endpoints
- Manage concurrent soft client connection licenses and enable “follow-the-sun” models to maximize utilization and reduce costs

End User Features

- Host and join point-to-point and multipoint conferences
- Add participants to a conference at any time
- Click-to-connect simplicity for easy B2B collaboration
- Lock, unlock, and PIN protect a conference
- Manage personal preferences, permissions and meetings
- Access and search the public directory
- Create personal speed-dial lists
- Initiate recording and webcasting of a conference, and browse recorded conferences

Multi-Tenant (Optional)

- Serve multiple private label tenants with unique URL access via a single VidyoConferencing infrastructure
- Configure policies to regulate inter-tenant and inter-portal meetings
- Assign VidyoRouter™, VidyoGateway™ and VidyoReplay™ resources to specific tenants

Specifications

	VidyoPortal™	VidyoPortal™ XL
Capacity	Registered Users: Up to 10,000 Active Uses: Up to 2,500 Tenants: Up to 25	Registered Users: More than 10,000 Active Uses: More than 2,500 Tenants: More than 25
Power Supply	Input: 100-240v ~, 4-2A, 50-60Hz Output: 250W Non-Redundant (auto-ranging)	Input: 100-240v ~, 3.5A, 50-60Hz Output: 2x 500W Redundant (auto-ranging, 80+ GOLD)
Dimensions and Gross Weight	Form factor - 1U Rack mount Dimensions (HxWxD) without ear and bezel Height - 1.67" (42.6 mm) Width - 15.5" (393.7 mm) Depth - 17.1" (431 mm) Weight - 17.76 lbs (8.058 kg)	Form factor - 1U Rack mount Dimensions (HxWxD) without ear and bezel Height - 1.69" (43.0 mm) Width - 17.09" (434.0 mm) Depth - 24.69" (627.1 mm) Weight - 35.02 lbs (15.9 kg)
Rack Support	ReadyRails™ static rails for tool-less mounting in 4-post racks with square or unthreaded round holes or tooling mounting in 4-post threaded and 2-post (Telco) racks	ReadyRails sliding rails with optional cable management arm for 4-post racks (optional adapter brackets required for threaded hole racks); ReadyRails static rails for 2-post and 4-post racks
Ports	2x RJ45 LAN ports - 100BASE-TX and 1000BASE-T 1x External Serial Port 2x USB2.0 Ports 1x eSATA Port 1x VGA Port	2x RJ45 LAN ports - 100BASE-TX and 1000BASE-T 1x External Serial Port 1x VGA Port 2x USB2.0 Ports
Operating Environment	Operating Temperature Range (for altitude ≤ 900m or 2952.75ft): 10°C to 35°C (50°F to 95°F) Non-Operating Temperature Range: -40°C to 65°C (-40°F to 149°F) Operating Humidity Range: 10% to 90% (non-condensing) Non-Operating Humidity Range: 5% to 95%	
Regulatory Compliance	Safety: EN 60950-1:2006, A11:2009 / IEC 60950-1:2005 ed2 EMC: EN 55022:2006 +A1:2007 / CISPR 22:2005 +A1:2005 +A2:2006 EN 55024:1998 +A1:2001 +A2:2003 / CISPR 24:1997 +A1:2001 +A2:2002 EN 61000-3-2:2006 +A1:2009 +A2:2009 / IEC 61000-3-2:2005 +A1:2008 +A2:2009 EN 61000-3-3:2008 / IEC 61000-3-3:2008 Australia C-TICK Class A; Argentina IRAM; Canada NRTL ICES Class A; China CCC Class A; Croatia KONCAR Class A; European Union CE Class A; Germany TUV IECEE IECEE CB; Israel SII Class A; Japan VCCI Class A; Mexico NOM; Moldova INSM Class A; Nigeria SONCAP; Norway NEMKO Class A; Russia GOST Class A; South Africa NRCS SABS Class A; South Korea KC Class A; Taiwan BSMI Class A; United States NRTL FCC Class A; Vietnam ICT Class A	Safety: EN 60950-1:2006 / IEC 60950-1:2005 ed2 EMC: EN 55022:2006 +A1:2007 / CISPR 22:2005 +A1:2005 EN 55024:1998 +A1:2001 +A2:2003 / CISPR 24:1997 (modified) +A1:2001 +A2:2002 EN 61000-3-2:2006 / IEC 61000-3-2:2005 (Class D) EN 61000-3-3:1995 +A1:2001 +A2:2005 / IEC 61000-3-3:1994 +A1:2001 +A2:2005 Australia C-TICK Class A, Argentina IRAM; Canada NRTL ICES Class A; China CCC Class A; Croatia KONCAR Class A; EU CE Class A; Germany TUV IECEE IECEE CB; Israel SII Class A; Japan VCCI Class A; Mexico NOM; Moldova INSM Class A; Nigeria SONCAP; Norway NEMKO Class A; Russia GOST Class A; South Africa NRCS SABS Class A; South Korea KC Class A; Taiwan BSMI Class A; United States NRTL FCC Class A; Vietnam ICT Class A



Vidyo, Inc. (Corporate Headquarters)

433 Hackensack Ave., Hackensack, NJ 07601, USA
Tel: 201.289.8597 Toll-free: 866.998.4396
Email: vidyoinfo@vidyo.com

EMEA

emea@vidyo.com
+33 (0) 488 718 823

APAC

apac@vidyo.com
+852 3478 3870

INDIA

india@vidyo.com
+91 124 4111671

www.vidyo.com