



LifeSize[®] Connections[™]

LifeSize Connections combines cloud-based simplicity with business-class performance in an HD video collaboration platform that is amazingly simple to deploy, making instant face-to-face collaboration possible with anyone, anywhere.

Cloud-Based Simplicity Meets Business-Class Performance

Extending high-definition (HD) video collaboration across the organization used to take days, or even weeks, and often required costly travel while straining IT resources. Now, in just minutes, you can make video collaboration available across your entire organization with LifeSize Connections. Cloud-based provisioning gives you the power to instantly connect remote employees to conference rooms so no one misses an important meeting again. Built-in firewall traversal enables secure company-to-company video calling with customers, suppliers and others, inside or outside your organization. And robust collaboration features – such as guest invitations, data-sharing and multi-party HD calling – ensure your organization's employees can get more done in less time.

All the while you can maintain complete administrative control from LifeSize Connections' web-based console, where you can add, reduce or reassign user accounts, run rich reports with full call data, and manage bandwidth settings for your network. LifeSize Connections is the cloud-based video collaboration solution you've been waiting for to unlock the power, productivity and quality of HD video collaboration for your organization.

LifeSize Connections. Amazingly simple, simply amazing.



Product Specifications – LifeSize[®] Connections[™]

Tangible Components

LifeSize Connections Software Client LifeSize Connections Web Administration Console LifeSize HD Video System (220 Series, LifeSize Passport, LGExecutive, powered by LifeSize) Webcam (not supplied) Microphone/headset (not supplied)

Service Components

9-way video/voice/text/data bridging Directory services/addressing Firewall/NAT traversal Automated deployment/configuration

Communications

56 Kbps - 3 Mbps configurable asymmetric transmit and receive bandwidths: 56 Kbps, 64 Kbps, 128 Kbps, 256 Kbps, 384 Kbps, 512 Kbps, 768 Kbps, 1024 Kbps, 1536 Kbps, 2048 Kbps, and 3072 Kbps

Video Features

Continuous presence 9-way HD video Video and audio mute Full screen Resizable window with multiple monitor support Picture in picture Layout control for dual stream video

Video Specifications/Resolutions

Support for transmit and receive 720p30, 576p30, 480p30, VGA, and 360p30

Support for 16:9 and 4:3 aspect ratios

Auto-bandwidth and resolution tuning with option for manual configuration of transmit and receive bandwidths

Actual resolution and frame rate depends upon capability of LifeSize HD Video System, PC/Mac configuration, webcam, remote end, and is impacted by the quality of the communications channel. In lower bandwidth environments, audio quality is prioritized over video.

Video Standards

H.264, H.263, and VPX

Video Formats

Automatic detection of 4:3 or 16:9 aspect ratios for transmitted and received video

Data Sharing

Transmit and receive content with other LifeSize HD Video Systems and software clients on the LifeSize Connections service. Share specific applications or your entire desktop.

Audio Features

High definition audio

Full duplex for natural conversation Echo cancellation and background noise reduction Configurable and automatic microphone gain In-client speaker and microphone test

Audio Standards

Siren7, Siren14, SILK, and μ -law

Administration Console Features

Management over LifeSize Connections user accounts and LifeSize HD Video System accounts Bandwidth controls with support for default (all users/systems) and specific settings per user/system

Easy import of new users/systems using .CSV format

Instant deactivation and/or reassignment of seats Reporting in aggregate and by user at Call Data Record level

Intelligent Networking Features

NAT/Firewall Traversal via integrated LifeSize® Transit[™] technology in software client, cloud, and LifeSize endpoints

Security

Encrypted signaling and all media Encryption algorithms: AES128, AES256, 168 3DES, DiffieHellman, and 1048RSA Encryption protocols: SSL, TLS, and SRTP

Directory and Address Book

Directory of all subscribed seats within deployment pushed to all users/systems within deployment automatically

Management

Centralized provisioning and management via LifeSize Connections Administrator Console (included) Soft Client and LifeSize Video Systems automatic provisioning Automated user communications

Recommended Peripherals

Webcams

Logitech B910 HD Webcam Logitech HD Pro Webcam C910 / C615 Logitech HD Webcam C525 / C510 / C310 / C270

Headsets Logitech ClearChat Pro USB

Logitech Premium Notebook Headset

USB Speakerphones

Logitech BSP420 USB Speakerphone Jabra® SPEAK™ 410 ClearOne CHAT™ 50, 100

Additional Software Client Features

Infinite guest user invite 1:1 and multi-way text messaging Account specific contact list Presence management Auto answer Block calls from specific users Missed call and new contact notifications Display name and user defined picon

Supported LifeSize HD Video Systems

Express 220, Team 220, Room 220, Passport, Passport Connect, and LG Executive running latest software

Minimum PC/Mac Requirements

Supported Operating Systems

Windows 7, Windows® Vista 32 and 64 bit, Windows® XP 32 bit with SP2, SP3 Mac OS X 10.6 and higher

CPU

PC/Mac: Intel Core 2 Duo 2.4 Ghz or higher (lower CPU will result in reduced performances)

Memory 1 GB minimum

Storage 60 MB available hard drive space



AMERICAS: 1601 S. MoPac Expressway Suite 100 Austin, Texas 78746 USA

Phone +1 512 347 9300 Toll Free +1 877 543 3749 www.lifesize.com EMEA: LifeSize Communications Toll-Free Europe 00 8000 999 09 799 APAC: LifeSize Communications Singapore Phone: +65 6303 8370

© 2011 Logitech. All rights reserved. Information contained in this document is subject to change without notice. LifeSize is the registered trademark or trademark of Logitech. All other trademarks are the property of their respective owners.