



DOME



Fixed IR Dome camera with motorized zoom and focus



Versatile, robust and sleek, fit for both the hardest outdoor and discreet indoor setups



Dynamic resolution up to 8MP (4K)



Built-in AI video and audio analytics and on-device storage



Factory-installed certificates backed by a trusted platform module (TPM)



Designed and developed in Norway and the UK

Image sensor 8MP (4K)

Image sensor size format 1/1.8"

Lens

Focal length: 3.6-10mm Aperture: f/1.5-f/2.8 Remote zoom and focus P-iris

Night vision

Automatic night mode IR-cut filter 850 nm IR LED

Field of view

100°-45° Horizontal 53°-25° Vertical

Maximum resolution & Frame rate 3840x2160@30fps

Dynamic range Multi-exposure line-based HDR

Video compression H.265, H.264, Motion JPEG

Audio

Microphone array (4x microphones) Al audio event classification Audio source localization

Security

Factory-installed certificates, no default passwords, mandatory access authentication, HTTPS/TLS encryption

Network protocols

IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD, NTP, RTSP, RTP, RTCP, ICMP, DHCP, ARP Streaming: RTP/UDP, RTP/RTSP/HTTPS/TCP

Power source

PoE+ (802.3at Type 2) For installation only: USB-C (1.5A mode)

Power consumption

Typical: 5 W Max without heater: 12.95 W Max with heater: 23 W

Storage MicroSD, SDXC UHS-I

Connection 802.3ab 10/100/1000 Gigabit Ethernet USB-C for preview and setup

Installation aid

Electronic leveler. Flexible bracket, mounts to standard back boxes. Refer to technical drawing.

Impact resistance

IK10 (IEC/EN 62262)

Water protection IP66 (IEC/EN 60529)

Temperature

Operating: -25C to +50C Storage: -40C to +60C Heater: 9.6W

Physical characteristics

Dimensions: 152x152x96mm Weight: 1.2 kg Body: Aluminum Adjustment range: Pan, Tilt, Azimuth

EMC


EN 55032, EN 61000-3-2/-3, EN 55024, EN 55035, EN 61000-6-1/-3, EN61000-6-2/-4, FCC Part 15B, ICES-003 Issue 6

Safety


IEC60950-1, IEC62368-1, IEC60950-22, UL/CSA60950-1, UL/CSA 62368-1, UL E164374, NOM-019, IEC62471(IR LED)

Technical drawings

Dome, side view



Mounting bracket, top view



	Designation	Dimension (mm)	Dimension (inch)
Α	Octagon	62.9 x 62.9 (88.9 diagonal)	2.47 x 2.47 (3.50 diagonal)
В	4″ Square Box	85.5 x 85.5 (120.9 diagonal)	3.36 x 3.36 (4.76 diagonal)
С	Single Gang	84.1	3.31
D	Double Gang	84.1 x 46	3.31 x 1.81
E	EU Ceiling Box	70	2.76
F	EU Outlet Box	60	2.36

Ordering information

Cloud Dome

Product family	PID	Product description
Cameras	DOME-W-5MP-30	Ava Aware Cloud camera - Dome white. 5MP resolution. 30 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-B-5MP-30	Ava Aware Cloud camera - Dome black. 5MP resolution. 30 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-W-5MP-60	Ava Aware Cloud camera - Dome white. 5MP resolution. 60 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-B-5MP-60	Ava Aware Cloud camera - Dome black. 5MP resolution. 60 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-W-5MP-120	Ava Aware Cloud camera - Dome white. 5MP resolution. 120 days retention. Al-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-B-5MP-120	Ava Aware Cloud camera - Dome black. 5MP resolution. 120 days retention. Al-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-W-4K-30	Ava Aware Cloud camera - Dome white. 8MP (4K) resolution. 30 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-B-4K-30	Ava Aware Cloud camera - Dome black. 8MP (4K) resolution. 30 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-W-4K-60	Ava Aware Cloud camera - Dome white. 8MP (4K) resolution. 60 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-B-4K-60	Ava Aware Cloud camera - Dome black. 8MP (4K) resolution. 60 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty.

Ordering information

On-prem Dome

Product family	PID	Product description
Cameras	DOME-W	Ava Dome Camera White. 8MP (4K) AI-powered dome camera, IR and advanced microphone array, indoor and outdoor, 3 year warranty.
Cameras	DOME-B	Ava Dome Camera Black. 8MP (4K) AI-powered dome camera, IR and advanced microphone array, indoor and outdoor, 3 year warranty.

Accessories

Product family	PID	Product description
Cameras	ACC-PEN-CAP-W	Pendant mounting cap for Ava Dome and 360 cameras. White.
Cameras	ACC-PEN-CAP-B	Pendant mounting cap for Ava Dome and 360 cameras. Black.
Cameras	ACC-MNT-ARM-W	Wall mount arm for Ava Dome and 360 cameras. White
Cameras	ACC-MNT-ARM-B	Wall mount arm for Ava Dome and 360 cameras. Black.
Cameras	ACC-POL-BRA-W	Pole mount for Ava Dome and 360 cameras. White.
Cameras	ACC-POL-BRA-B	Pole mount for Ava Dome and 360 cameras. Black.
Cameras	ACC-CRN-BRA-W	Corner mount for Ava Dome and 360 cameras. White.
Cameras	ACC-CON-A34-W	Conduit adapter 3/4" for mounting ¾" NPT or NPS electrical conduits to the camera for cable protection. White.
Cameras	ACC-CON-A34-B	Conduit adapter 3/4" for mounting ¾" NPT or NPS electrical conduits to the camera for cable protection. Black.
Cameras	SVCS-CAM-W5YR	5 year total warranty, with next business day advance replacement. Purchased at the time of original purchase.