







## AVer VB130

# Simply brighter and better 4K Video bar with intelligent lighting for Huddle Rooms



### **Product Specifications**

#### **Camera**

- · 4K optics lens, 120° FOV, up to 4X zoom
- · Sony 4K sensor: ultra-crystal-clear image in any lighting
- Frame rates: (16:9) 4K 30fps; 1920 x 1080, 1600 x 900, 1280 x 720, 960 x 540, 848 x 480, 800 x 448, 640 x 360, at 60, 30, 15fps; (4:3) 1280 x 960, 800 x 600, 640 x 480 at 60, 30, 15fps
- · Adjustable audio fence: freedom to define your meeting area
- Intelligent fill light: Automatically adjust lighting level to make you look energetic in virtual meetings in a dim environment\*
- SmartFrame: automatic FOV adjustment (auto focus) to fit all participants
- SmartSpeaker: Voice triggered tracking people or specific preset areas.
- True WDR up to 120db: 3D noise-reduction and superb backlight compensation optimize lighting in high-contrast conditions
- Mirror, flip, AE, white balance: auto/manual override via PTZApp2
- · Minimum focus distance: 60 cm
- People-counting API: enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
- 10 camera presets (through remote control and IP web page)
- \*The best lighting distance is for people sitting within 1meter far from the camera

#### **Audio**

- Beamforming microphone array: 5 microphones, 4 m pickup range
- · Echo cancellation and background noise suppression
- · Supports expansion microphone
- 6Wx1 speaker with professional bass port tuned for communication
- 180Hz 20kHz Speaker frequency response
- · Output volume: 94dB SPL +/-2dB at 0.5 meter

#### **Connectivity**

- · 12V/2A power adapter
- · Mini-B for expansion microphone connection
- USB Type-B 3.1 connector, backward compatible with USB 2.0
- RJ45 port for Ethernet
- USB 2.0 Type-A for wireless connection\*

#### **Video Format**

- · YUV, YUY2, MJPEG
- · Network video compression format: H.264
- · Network protocols: RTSP, RTMP\*

#### **USB**

- · 3.1 Gen 1, backward compatible with USB 2.0
- UVC 1.1 (USB video), UAC 1.0 (USB audio)

#### **Control**

- · IR remote control
- WebUI: IP access via Chrome browser (Chrome 76.x or later; Internet Explorer not supported)
- · UVC/UVA plug-and-play
- · PTZApp 2

#### **Mount**

- · Screen mount kit
- · Camera wall-mount bracket

#### **System Requirement**

- · Windows® 7/10
- · MacOS X 10.7 or later
- Google Chromebook™ version 29.0.1547.70

#### **Hardware Specs**

- · 3.2 GHz Intel® Core™ i5-4460 processor
- · 4 GB RAM or more
- · USB 3.1 port, backward compatible with USB 2.0

#### **Power Supply**

- AC 100V-240V, 50/60 Hz
- · Consumption: 12V/2A

#### **Free Applications for Meeting Collaboration**

(Free Apps support on Windows® and Mac® computers)

#### EZManager 2: Camera Central Management Software

 Remotely group FW/SW upgrades, control the camera, and manage settings

#### PTZApp 2: Camera Setting Software

- View live video, people counting number, meeting interval information
- · Enable Skype for Business far-end control
- · Upgrade firmware automatically or manually
- Control the camera
- · Set parameters and adjust the camera image
- · Diagnose operating status

#### EZLive: Broadcasting Software

 Enjoy multi-camera real-time streaming, annotating, image capturing, and video recording

#### **Environmental Data**

- Operation temperature: 0 ~ 40°C
- · Operation humidity: 20% ~ 80%
- Storage temperature: -20 ~ 60°C
- Storage humidity: 20% ~ 80%

#### **Dimensions**

- · Package dimensions: 406(L)x146(W)x189(H) mm
- · Package weight: 2.358 kg
- Camera: 350(L) x 65(H) x 75(D) mm/0.922 kg
- · Remote control: 149.72 x 42.3 x 19.29 mm/50g

#### **Package Contents**

- · VB130 unit
- Power cable 10 ft (3 m)
- USB 2.0 Type-B to Type-A Cable 15 ft (5 m)
- QR code card
- Screen mount or wall mount\*
- Remote control
- Tripod screw

\*Availability varies based on location. Please check with your local agent for details.

<sup>\*</sup>Optional wireless dongle is required to connect with mobile phone

<sup>\*</sup>When USB streaming is in use, RTSP and RTMP are not available.

#### **Optional Accessories**

- · Wall mount and mounting screws
- · Screen mount kit
- · BT Dongle
- · 10m/20m expansion microphone
- 10m/20m/30m USB 3.1 extension cable
- USB 3.1 GEN1 Type-B to Type-A cable, 3 m

#### Warranty

- · Camera: 3 years
- · Accessories: 1 year

#### **Compatible Applications**

Microsoft® Teams, Skype for Business, Skype, Zoom, Google Meet™, Intel® Unite™, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting®, TrueConf, Adobe® Connect, Cisco WebEx®, Fuze, GoToMeeting™, Microsoft® Lync™, Vidyo, vMix, WebRTC, Wirecast, XSplit


\*For 4K UHD support, please check system/hardware requirements with your software application provider.

\*\*Specifications may vary depending on countries and are subject to change without notice.

#### **Product Overview**



#### Side



#### Angle-adjustable screen mount





