ClickShare CX-20

Transform small meeting rooms and huddle spaces into inspiring conference facilities.



- Full BYOD support
- Remote collaboration
- Triple agnostic: works with any device, and UC technology and any brand of AV peripheral
- Enhanced security
- Connected and cloud managed
- Delivered with 1 Conferencing Button
- Collaborate with Conferencing Button or Collaboration App

The modern world of enterprise requires smooth collaboration and flexibility, especially when it comes to team meetings in huddle rooms, and this is exactly what Barco ClickShare CX-20 provides. Encouraging creative innovation through seamless wireless conferencing, ClickShare CX-20 can make meetings more inspiring and more productive.

Find out what's new in the latest ClickShare update

Start a huddle meeting from your device

With ClickShare CX-20, it's easier than ever to start remote huddle meetings from your device, bringing a seamless and immersive conferencing experience to all participants, whether local, guest or remote. Use your preferred conferencing software combined with the ClickShare Conferencing Button and you can start your conference in less than seven seconds. The CX-20 connects wirelessly to existing huddle room cameras, speakerphones and audio peripherals, saving time and maximizing efficiency.

Decide how you want to collaborate

ClickShare CX-20 provides you with exceptional flexibility and choice, enabling you to decide just how you want to collaborate. Whether you're on PC, Mac or mobile, the ClickShare Wireless Conferencing Button and ClickShare Collaboration App facilitate a user experience that's both straightforward and consistent. In addition to its multi-device compatibility, ClickShare CX-20 is also fully compatible with your conferencing platform (UC) technology and your brand of USB-peripherals. Additional features such as local view of the room display help to optimize the experience.

Enhanced security and seamless integration

A perfect fit for any business environment, the ClickShare CX-20 wireless conferencing system comes equipped with a selection of great features for enhanced security and seamless integration. ClickShare Conference provides hassle-free integration with any IT network, while the XMS (Cloud) Management Platform provides for easy device management, as well as an intuitive user experience and clear analytics to get more out of your digital workspace.



PRODUCT SPECIFICATIONS ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 m Power supply Standard 110/220 V AC plu

| Dimensions (HxWxD) | 34 mm x 135 mm x 135 mm |
|--|---|
| Power supply | Standard 110/220 V AC plug |
| Power consumption | Operational: 5-10W, 24W Max |
| Weight | 900 gr |
| General specifications | |
| Operating system | Windows 8/8.1/10. macOS 10.13 and higher. Android v9 and higher (ClickShare App)* iOS 12 and higher (ClickShare App)* |
| Video outputs | 4K UHD (3840*2160) @ 30Hz. HDMI 1.4b |
| Audio output | USB, HDMI |
| USB | 1 X USB-A, 1 X USB-C |
| Clickshare Buttons | 1 |
| ClickShare App | Desktop & Mobile* |
| Native protocols | Airplay, Google Cast, Miracast* |
| Noise Level | Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C |
| Authentication protocol | WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode |
| Wireless transmission protocol | IEEE 802.11 a/g/n/ac and IEEE 802.15.1 |
| | |
| Reach | Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) |
| Reach Frequency band | ClickShare Base Unit |
| | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) |
| Frequency band | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit |
| Frequency band Connections | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m |
| Frequency band Connections Temperature range | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing |
| Frequency band Connections Temperature range Humidity | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing |
| Frequency band Connections Temperature range Humidity Anti-theft system | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock |
| Frequency band Connections Temperature range Humidity Anti-theft system Certifications | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE |
| Frequency band Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE / |
| Frequency band Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity Room Dock (peripheral support) | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE / Yes |
| Frequency band Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity Room Dock (peripheral support) Local view & moderation | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE / Yes Local view of the room display only |
| Frequency band Connections Temperature range Humidity Anti-theft system Certifications Touch screen support & Interactivity Room Dock (peripheral support) Local view & moderation Network connection | ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz (DFS) 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Kensington lock FCC/CE / Yes Local view of the room display only LAN & WiFi * |

Last updated: 13 Jul 2020

 $Technical \ specifications \ are \ subject \ to \ change \ without \ prior \ notice. \ Please \ check \ www.barco.com \ for \ the \ latest \ information.$

