

# OverView OSV-560F

Long lifetime seamless flat 6.2 megapixels collaboration video wall



The OverView OSV-560F is a high-performing video wall, ideal to visualize and evaluate huge amounts of information in 24/7 environments. Featuring a large, flat, panoramic seamless canvas, a mix of data and video can be displayed simultaneously in high quality without the interruption of a seam or a bezel.

Furthermore, by benefiting from proven rear-projection technology, state-of-the-art controllers and advanced signal processing, the OSV offers a feature-rich solution with high image quality and excellent reliability. Compact in setup, this video wall suits a multitude of possible applications from crisis operations and war rooms, to brainstorm and planning rooms, and of more traditional control room applications in utilities, energy and process control.

### All the advantages of LED technology

Images are displayed on the OSV using Barco's LED-lit rear-projection technology, which has a long track record in the control rooms market. This means these seamless video walls benefit from the many advantages of LED technology, including: very low maintenance, substantially reduced power consumption, and long lifetime. The use of DLP projection technology makes the solution fit for 24/7 use, preventing the image retention (e.g. a burned-in company logo) often seen in less qualitative solutions. The OSV-560F consists of five blended rear-projection cubes, forming one seamless image.

### TransForm C: positioning content made really easy

TransForm C, OSV's controller and collaboration management system, allows users to drag-and-drop sources freely onto the screen. The sophisticated intelligence of the system, combining auto-generated and content-type dependent layout regions, always provides the ideal collaboration composition on the canvas and ensures

optimal usage of the display surface.

In addition, direct integration of a Barco ClickShare wireless presentation system allows users to display content from their laptop, smartphone or tablet in its full native resolution on the video wall by simply clicking a button. Depending on the configuration, up to eight users can use ClickShare to share content on the OSV.

**PRODUCT SPECIFICATIONS****OVERVIEW OSV-560F**

Resolution	6.2 Mega Pixels
Pixel size	1 mm
Brightness	80 Nit (cd/m <sup>2</sup> )
System contrast	25:1 with 100 lux ambient light on-screen
Color	Up to 165% EBU
Display technology	Rear projection DLP
White point	2,300K   6,500K   9,300K   arbitrary
Brightness uniformity	90% ANSI 9
Color stability	Self calibrating with spectrometer based Sense6
Screen	Barco Semi-Rigid Seamless Rear Projection Screen
Screen gap	None. No seams or bezels
Screen size	4415 (length) x 1400 (height) mm 173.8 (length) x 55 (height) inch
Radius	N/A - flat screen
H / V half gain angle	60° both horizontal and vertical
Screen reflectivity	2%
Dimensions (physical)	5214 (length) x 2370 (height) mm 205 (length) x 93.3 (height) inch
Image start height	750 mm / 29.5 inch above floor
Depth	Center: 1170 mm / 46 inch
Weight	830 kg / 1830 lbs
Light source	6x redundancy for each of 3 LEDs
Light source lifetime	> 60,000 h > 80,000 h (eco)
Recommended maintenance interval	> 5 years No burn-in, no image retention
Conditions for operation	10°C-40°C, 50°F-104°F 80% humidity (non condensing)
AC input voltage	110 – 240 V, 50-60Hz
Power	Typical: 1780 W ; Maximum: 2450 W
Heat dissipation	Typical: 6079 BTU/h ; Maximum: 8367 BTU/h
Signal inputs	Twin dual link DVI-D
Input frequency	300 MHz
Integration to third party equipment	Web based API
Warranty	2 years

Last updated: 03 May 2017

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.