

Cisco TelePresence MSE 8000

Figure 1. Cisco TelePresence MSE 8000



Cisco TelePresence MSE 8000

Product Overview

The Cisco TelePresence[®] MSE 8000 (MSE 8000) is a high-capacity voice and video conferencing media services engine. This powerful, fault-tolerant solution is ideal for the large-scale communication needs of large enterprises and service providers requiring a high-availability, high-performance, scalable solution.

Features and Benefits

The super robust Cisco TelePresence MSE 8000 is a high-capacity, carrier-class, voice and video conferencing chassis and has a system supervisor; hot-swap feature blades; and redundant, monitored power supplies and cooling system with the features listed in Table 1. Table 2 lists the components of the Cisco TelePresence MSE 8000.

Table 1. Cisco TelePresence MSE 8000 Feature Summary

Feature	Benefit
Design features	<ul style="list-style-type: none"> • Ten hot-swappable option slots • High-definition (HD) conferencing, recording, and gateway capabilities • Redundant and hot-swappable fan trays and power supplies • Dual 48-volt power option • Active environmental monitoring • High-speed backplane to create multiple multiblade multipoint control units (MCUs) and telepresence servers • Supervisor blade for system management and configuration • Extensive approvals and compliance
Application features	<ul style="list-style-type: none"> • Offers multiple and interchangeable functions, including media, recording, and gateway blades • Extends the capabilities of large service providers by providing feature-rich conferencing, recording, and ISDN gateway, as well as system management and configuration in an all-in-one device • Integrated with Cisco TelePresence Management Suite

Feature	Benefit
Support capabilities*	<ul style="list-style-type: none"> • Up to 180 ports of HD 1080p multipoint • Up to 720 ports of standard-definition (SD) multipoint • Up to 72 ISDN Primary Rate Interface (PRI) instances • Up to 90 recording ports • Up to 360 IP gateway calls • Up to 144 Cisco TelePresence screens • More than 1 Gbps of conferencing bandwidth • Wide range of protocols supported, including H.323, Session Initiation Protocol (SIP), and H.320 • Advanced Encryption Standard (AES) encryption • Standards-based and compatible with all major vendors' endpoints • Support for Cisco TelePresence Multiway technology

* Optional feature blades required

Table 2. Cisco TelePresence MSE 8000 Components

System Components	Description
Cisco TelePresence MSE 8000	<ul style="list-style-type: none"> • 10-slot media services engine chassis with high-speed backplane
Cisco TelePresence MSE 8010 fan tray	<ul style="list-style-type: none"> • Hot-swap fan tray (for use in both top and bottom slots) with environmental monitoring
Cisco TelePresence AC Power Option	<ul style="list-style-type: none"> • Dual redundant 100–240 VAC power supply shelves • NIC power shelf management module units • 1-kW AC/DC rectifier modules
Cisco TelePresence Supervisor MSE 8050	<ul style="list-style-type: none"> • Supervisor blade, required for system management and configuration

Licensing

Software licenses are required in the Cisco TelePresence MSE 8000 chassis to enable the functions of individual blades. Refer to Table 3 for details.

Table 3. Cisco TelePresence MSE 8000 Software License

Chassis Software Licences	Description
MSE-8710-SL TelePresence Server screen license	<ul style="list-style-type: none"> • Required in Cisco TelePresence MSE 8000 chassis to enable one TelePresence screen when allocated to the Cisco TelePresence Server MSE 8710
MSE-8420-PL MCU (Media) port license	<ul style="list-style-type: none"> • Required in Cisco TelePresence MSE 8000 chassis to enable one SD video port and one additional audio port when allocated to the Cisco TelePresence MCU MSE 8420 • Two required in Cisco TelePresence MSE 8000 chassis to enable one HD 720p30 video port and one additional audio port or two SD videos ports and no additional audio ports when allocated to the Cisco TelePresence MCU MSE 8510 • Four required in Cisco TelePresence MSE 8000 chassis to enable one HD 1080p30 video port and one additional audio port when allocated to the Cisco TelePresence MCU MSE 8510
MSE-8350-PL IP GW port license	<ul style="list-style-type: none"> • Required in Cisco TelePresence MSE 8000 chassis to enable two IP GW calls of which one can be transcoded when allocated to the Cisco TelePresence IP GW MSE 8350
MSE-8310-PL PRI port license	<ul style="list-style-type: none"> • Required in Cisco TelePresence MSE 8000 chassis to enable one ISDN PRI port when allocated to the Cisco TelePresence ISDN GW MSE 8321
MSE-8220-PL Recording port license	<ul style="list-style-type: none"> • Required in Cisco TelePresence MSE 8000 chassis to enable one recording port when allocated to the Cisco TelePresence VCR MSE 8220

Product Specifications


Table 4 lists the product specifications for the Cisco TelePresence MSE 8000.

Table 4. Product Specifications

Feature	Specification
Product compatibility	<ul style="list-style-type: none"> Standards-based and compatible with all major vendors' endpoints
Software licenses	<ul style="list-style-type: none"> The port licensing model offers added flexibility. Port licenses are purchased for the Cisco TelePresence MSE 8000 to enable screen and port functions. Port licenses are stored in the chassis, and the Cisco TelePresence Supervisor MSE 8050 can allocate licenses to slots. Optional feature blades must be inserted into slots to use software licenses.
Chassis	<ul style="list-style-type: none"> Fault-tolerant, high-availability chassis Ten hot-swappable option slots Redundant power inputs and hot-swappable fan trays Dual independent 48-volt DC power inputs Active environmental monitoring High-speed backplane and management bus
AC power supply	<ul style="list-style-type: none"> Two independent AC power shelves convert power for the two DC power inputs of the chassis. Each shelf has multiple redundant hot-swap rectifier modules. Each rectifier has its own independent AC inlet.
Cisco TelePresence Supervisor MSE 8050	<ul style="list-style-type: none"> Actively monitors and manages the chassis and blades Hot-swappable without affecting feature blade operation Configures blades and monitors the status of blades, fans, air filters, power feeds, and AC power supply shelves Alert generation Standard telco alarm connector Management through built-in web server RS-232 for local control and diagnostics Strong password policy Syslog for diagnostics Configuration backup over network Secure upgrades through Ethernet or CompactFlash Supports Simple Network Management Protocol (SNMP) Audit log
Optional feature blades	<ul style="list-style-type: none"> The following feature blades can be slotted into a powered Cisco TelePresence MSE 8000 chassis: <ul style="list-style-type: none"> Cisco TelePresence Server MSE 8710: Up to 16 screens of HD telepresence conferencing Cisco TelePresence MCU MSE 8510: Up to 20 ports of HD video plus 20 ports of voice multipoint conferencing, or up to 80 ports of SD video multipoint conferencing Cisco TelePresence MCU MSE 8420: Up to 40 ports of SD video plus 40 ports of voice multipoint conferencing Cisco TelePresence IP GW MSE 8350: Up to 20 transcoding and 20 nontranscoding video calls Cisco TelePresence ISDN GW MSE 8321: Up to 8 E1 or T1 ISDN primary rate interfaces Cisco TelePresence VCR MSE 8220: Up to 10 ports of video recording with streaming server <p>Note: Refer to individual data sheets for detailed description of blades.</p>
Language	<ul style="list-style-type: none"> English as standard; alternative language packs can be loaded onto the system
Physical dimensions (H x W x D)	<ul style="list-style-type: none"> Physical dimensions: 33.25 x 17.2 x 20.5 in. (842 x 437 x 520 mm) (19 rack units [19RU]) 19-in. rack-mountable (kit supplied)
Weight	<ul style="list-style-type: none"> 110 lbs (50 kg)
Power	<ul style="list-style-type: none"> -48 VDC, 100–240 VAC 50/60 Hz

Feature	Specification
Environmental data	<ul style="list-style-type: none"> Operating temperature: (0 to 35°C) ambient Relative humidity below 95% (noncondensing)
Approvals and compliance	<ul style="list-style-type: none"> European safety: EN 60950-1 USA/Canada safety: UL 60950-1 CB, CE EMC: EN55022 class A, ETS EN300 386, EN61000-3-2 <ul style="list-style-type: none"> EN61000-3-3, EN55024: EN61000-4-2,-3,-4,-5,-6,-11 FCC Part 15 class A, VCCI class A, AS/NZS 3548 <ul style="list-style-type: none"> CCC - GB4943, GB9254 YD/T993 Telecoms: <ul style="list-style-type: none"> USA: 47 CFR Part 68, Canada: IC CS-03, Issue 9, Part VI Europe: ETS 300 046-3, TBR 4 Japan: Ordinance of MPT No 31 Australia – S038 China: NAL RoHS compliant

Figure 2. Example of endpoints and network supported by Cisco TelePresence MCUs



Warranty Information

Find warranty information on Cisco.com at the [Product Warranties](#) page.

Ordering Information

To place an order, visit the [Cisco® Ordering Home Page](#) and refer to Table 5 or contact your local Cisco representative. To download software, visit the [Cisco Software Center](#).

Table 5. Ordering Information

Product Name	Part Number
Cisco TelePresence MSE 8000 chassis	CTI-8000-MSECH-K9
Air Filter Kit MSE 8000 Chassis, 4 Air Filters	CTI-8000-4AIRF=
1kW AC/DC Power Shelf Rectifier Module	CTI-8000-VALRCTF=
1 Additional MSE-8710-SL TelePresence Server Screen License	L-8710-1SL
2 Additional MSE-8420-PL MCU (Media) Port Licenses	L-8420-2PL
1 Additional MSE-8350-PL IP GW Port License	L-8350-1PL
1 Additional MSE-8310-PL PRI Port License	L-8310-1PL
1 Additional MSE-8220-PL Recording Port License	L-8220-1PL

Cisco Services

Cisco and our partners provide a broad portfolio of intelligent, personalized services and support that can help you realize the full value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation through a network-based collaboration platform that enables businesses to collaborate anywhere, anytime. For more information about these services, please visit: <http://www.cisco.com/go/telepresenceservices>.

For More Information

For more information about the Cisco TelePresence MSE 8000, please visit <http://www.cisco.com/go/telepresence> or contact your local Cisco account representative or authorized Cisco partner. Product specifications are estimates and subject to change without notice.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)