LightScene EV-100



DATASHEET / BROCHURE

















2,000-lumen WXGA accent lighting projector in white, with a low visual noise design, ideal for retail displays, galleries and museums.

Add movement and life to your retail displays or exhibitions with a low visual noise projector that blends in beautifully to any environment, and blurs the line between lighting and projection with 2,000-lumen brightness and WXGA sharpness.

A discreet attention-grabber

The LightScene EV-100 allows you to to create instantly appealing visuals with sharp WXGA resolution and 2,000-lumen brightness. Yet thanks to its low visual noise white casing, it can be used where a traditional projector would stand out, such as window displays and as part of exhibitions.

Simple, flexible implementation

A light, flexible design means the EV-100 can be installed in a variety of ways, from a traditional ceiling mount to a freestanding floor mount, or attached to an existing lighting track like a spotlight¹. It can also be mounted at and project from any angle, including portrait. The projector can be used as a traditional spotlight for when simple lighting effects are needed.

Easy to program and use

The EV-100 comes with Epson Projector Content Manager Software for quick, easy set-up without specialist installation. Playlists can easily be loaded via SD Card and changed using remote control by employees without the need for a computer. The projector can also use advanced techniques such as edgeblending to achieve stunning results in larger spaces that require multiple-unit installations.

Fit and forget reliability

A five-year, 20,000-hour warranty, coupled with Epson's durable, reliable inorganic phosphor wheel technology means that EV-100 projectors can be installed and forgotten about, and don't require regular maintenance.

KEY FEATURES

- Discreet signage projector
 Low visual noise white casing won't grab the spotlight
- Sharp, vivid projection
 2,000-lumen brightness and detailed
 WXGA resolution
- Flexible installation
 Can be ceiling-mounted, floor-standing or attached to a lighting track
- Easy playlist loading
 Playlist can be loaded from an SD Card without the need for a computer
- Fit and forget reliability
 Durable Epson technology supported by a five-year 20,000-hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology LCD Panel 0,59 inch with C2 Fine

IMAGE

Colour Light Output 2.000 lumen (economy) in accordance with IDMS15.4

White Light Output 2.000 lumen - 1.000 lumen (economy) in accordance with ISO 21118:2012

Portrait Colour Light Output 2.000 lm
Portrait White Light Output 2.000 lm

Resolution WXGA, 1280 x 800, 16:10

 Aspect Ratio
 16:10

 Contrast Ratio
 2.500.000 : 1

 Native Contrast
 1.200 : 1

 Light source
 Laser

Laser Light source 20.000 Hours Durability High, 30.000 Hours Durability Eco

Keystone Correction Manual vertical: \pm 45 $^{\circ}$, Manual horizontal \pm 40 $^{\circ}$

Colour Reproduction 16.77 million colours

OPTICAL

Projection Ratio 1,38 - 2,19:1

Zoom Motorized, Factor: 1 - 1,58

Projection Lens Zoom Ratio 1,38 - 2,19 : 1 Lens Optical

Image Size 30 inches - 133 inches
Projection Distance Wide 0,9 m - 4 m

 Projection Distance Wide
 0,9 m - 4 m

 Projection Distance Tele
 1,4 m - 6,3 m

 Projection Distance Wide/Tele 0,88 m - 6,34 m
 1,51 - 1,92

 Focal Distance
 18,2 mm - 28,4 mm

 Focus
 Motorized

CONNECTIVITY

Interfaces USB 2.0 Type A, USB 2.0 Type B (Service Only), Ethernet interface (100 Base-TX / 10 Base-T),

Wireless LAN b/g/n (2.4GHz), HDMI in, Stereo mini jack audio out, SD Card Slot, SD Card

playback

ADVANCED FEATURES

Security Wireless LAN security, Password protection

Features Digital zoom, Horizontal and vertical keystone correction, Quick Corner

Video Colour Modes Dynamic

Projector control via: Crestron (Network)

GENERAL

Energy Use 170 W, 118 W (economy), 0,3 W (standby)
Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions (default 530 x 470 x 250 mm (Width x Depth x Height)

position)

Dimensions: Projection Unit Ø175 x 260 mm (Depth)

Dimensions: Power Supply 361 x 110 x 65 mm (Width x Depth x Height)

Product weight 5 kg
Direct Mount weight 1,9 kg

 Noise Level
 Normal: 34 dB (A) - Economy: 22 dB (A)

 Temperature
 Operation 5° C - 40° C, Storage -10° C - 60° C

 Humidity
 Operation 20% - 80%, Storage 10% - 90%

Colour White

OTHER

Warranty 60 months Carry in or 20.000 h
Optional warranty extension available

LightScene EV-100

WHAT'S IN THE BOX

- Cable cover
- Direct mount unit
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set



OPTIONAL ACCESSORIES

- Lighting Track Mount ELPMB54W EV-100 V12H933W40
- Floor Stand ELPMB55W EV-100 V12H888W10

LOGISTICS INFORMATION

SKU	V11H868040
EAN code	8715946647487
Country of Origin	China



Epson Deutschland GmbH Otto-Hahn-Str. 4 D-40670 Meerbusch Info-Line: 02159 92 79 500 Telefax: +49 (0) 2159/538-3000 www.epson.de

Epson in Österreich Info-Line: 01 253 49 78 333 www.epson.at Epson in der Schweiz Info-Line: 022 592 7923 www.epson.ch

1. Floor stand and lighting track are purchasable options.

LightScene EV-100

