

ProLine+ Touchscreen



An indescribable experience

The ProLine+ is the next generation of touchscreens, bringing your lessons to life! It includes ProWrite Ink for a natural writing experience: it will feel as fluent as writing with pen on paper. Easily navigate to all main features of your touchscreen with Prowise Central. The ProLine+ is the result of years of experience and knowledge of education and ICT.

65": PW.1.14065.0001 | 75": PW.1.14075.0001

Screen	65"	75"
Bezel color	Brushed aluminium (grey)	Brushed aluminium (grey)
Diagonal	65 inch	75 inch
Panel type	Ultra HD LED - IPS	Ultra HD LED - IPS
Resolution	3840 x 2160 @ 60Hz	3840 x 2160 @ 60Hz
Glass plate	Anti-Glare Pro	Anti-Glare Pro
Glass thickness	4 mm / 0.16 inches	4 mm / 0.16 inches
Glass hardness	Mhos 7	Mhos 7
Aspect ratio	16:9	16:9
Contrast ratio	1200:1	1200:1
Brightness	350 cd/m ²	410 cd/m ²
Number of colors	10 Bit (1.07B)	10 Bit (1.07B)
Viewing angle	178°	178°
Panel refresh rate	60Hz	60Hz
Modules	65"	75"
PC module slot	Yes, OPS slot	Yes, OPS slot
Touch type	65"	75"
Type	IR-pro + EMR	IR-pro + EMR
Multi-touch	Yes (20 points)	Yes (20 points)

Multi-writing	Yes (10 points)	Yes (10 points)
Auto-calibration	Yes	Yes
Resistant to sunlight	Yes	Yes
Supported OS	Windows 7, 8.1 & 10/Mac OS/Linux/Android and Chrome OS	Windows 7, 8.1 & 10/Mac OS/Linux/Android and Chrome OS
Audio	65"	75"
Speakers	3-Way speaker	3-Way speaker
Power	2 x 14W/ 8Ω	2 x 14W/ 8Ω
Microphone	Yes, Wide-area	Yes, Wide-area
Prowrite pen technology	65"	75"
Active Pen	Yes, ProWrite Ink	Yes, ProWrite Ink
Pressure sensitivity	Yes (up to 2048 levels)	Yes (up to 2048 levels)
Connectivity	EMR	EMR
Power	Charging station (Automatic charging)	Charging station (Automatic charging)
Hoover function	Yes	Yes
Angle recognition	N/A	N/A
Palm rejection	Yes	Yes
Windows ink support	Yes	Yes
Special features	65"	75"
Prowise Central	Yes, no external app support	Yes, no external app support
Over the Air Updates (OTA)	Yes	Yes
NFC Reader/Writer	Yes	Yes
Pen Charging station	Yes, automatic charging	Yes, automatic charging
Connections	65"	75"
HDMI 2.0	2	2
HDMI 2.0 (CEC and ARC)	1 (With CEC and ARC support)	1 (With CEC and ARC support)

Display port 1.2	1	1
Audio output analog	1 (3.5mm headphone Jack PJ3591 female)	1 (3.5mm headphone Jack PJ3591 female)
Audio output digital	Coaxial (fixed)	Coaxial (fixed)
RS232 control	1 (Sub-D, 9 pins)	1 (Sub-D, 9 pins)
AV in	N/A	N/A
USB touch port	1 (USB-B female)	1 (USB-B female)
USB 2.0	1	1
USB 3.0	2	2
Webcam Mount + top USB	Yes	Yes
Wi-Fi for online updates	Yes	Yes

General information	65"	75"
Voltage	~ 100-240 V (50/60Hz)	~ 100-240 V (50/60Hz)
Nominal power consumption (without modules)	350W	450W
On mode power consumption (Energy Star enabled)	108.47W	-
On mode power consumption (Energy Star disabled)	120W	194W
Stand-by power consumption	≤ 0,5 Watt	≤ 0,5 Watt
Gross weight	82 kg / 180.8 lbs	80 kg / 176.4 lbs
Netto weight	69 kg / 152.1 lbs	59 kg / 130 lbs
Dimensions of the screen (W x H x D)	1533.8 x 973.8 x 94.8 mm / 60.4 x 38.3 x 3.7 inches	1762 x 1062 x 100 mm / 69.4 x 41.8 x 3.9 inches
Dimensions of the packaging (W x H x D)	1665 x 1062 x 210 mm / 65.5 x 41.8 x 8.3 inches	1931 x 1235 x 280 mm / 76 x 11 x 48.3 inches
VESA standard	VESA 800 x 600 mm	VESA 800 x 400 mm
Certifications	CE: EMC+LVD/FCC-IC/RoHS/UL+CB, RCM and Energy Star	CE: EMC+LVD/FCC-IC/RoHS/UL+CB and RCM
Warranty	7 years	7 years

Environmental conditions	65"	75"
Operation temperature	0°C - 38°C / 32 - 100°F	0°C - 38°C / 32 - 100°F

Storage temperature	-20°C - 60°C / -4 - 140°F	-20°C - 60°C / -4 - 140°F
Storage humidity	10% - 90%	10% - 90%
Operation humidity	10% - 90%	10% - 90%