



Easy
Meet anyone,
anywhere, anytime



Point-to-point
Unlimited calling



HD voice & video
Exceptional quality



Screen sharing
Collaborate on
content



Contacts
Scroll and search
directories and
personal contacts



Guest invite
Invite anyone to join
you on video



QuickMeet™
Hold instant
multiparty meetings



QuickConnect™
Plug and play
installation



Call+
Transfer, hold,
forward, call history
and do not disturb



Favorites
Speed dials with
availability



Interoperable
Works with Cisco,
Skype for Business/
Lync, Lifesize, Polycom,
H.323/SIP



SmartPath™
Intelligent routing
and quality control



Video mail
Send and receive
personal video
messages



Join now
See today's meetings
and join instantly



Secure
End-to-end encryption
with secure connection
at all times



Auto upgrade
Always on the
latest version



EVERYTHING YOU NEED TO KNOW

Designed to work in tandem with a StarLeaf meeting room system and its touchscreen controller, the StarLeaf Conference Phone 2220 sends and receives flawless audio. It enriches the whole meeting experience with natural acoustics to ensure everyone hears and is heard clearly, no matter where they are in the room.

Highlights for your business

- Increases business meeting efficiency
- Easy to use
- Everyone enjoys a natural ambience
- Sound quality equivalent to face-to-face discussions
- Intelligently isolates and picks out the person speaking
- Automatically eliminates background noise interference

@ a Glance

- A powerful and highly sensitive speakerphone and microphone, controlled by the StarLeaf Touch 2035
- Designed for use with StarLeaf meeting room systems
- Great for all rooms including larger boardrooms, and where excellent sound quality is essential
- Provides:
 - Four directional microphones
 - Voice mute
 - Full-duplex speakerphone
 - Wideband audio
 - Support for up to two satellite StarLeaf Telepresence Microphones 0155

TECHNICAL SPECIFICATIONS

Physical

Weight 2.2lbs/990g

Dimensions: (H x W x D)

2.75" x 10.25" x 10.25" /
70mm x 260mm x 260mm

Power

Built-in autosensing power over Ethernet (power injector included)
Provides power to attached touchscreen controller

Speakerphone

Full-range, audio loudspeaker
Resonance-free, critically-damped speaker enclosure
Response: 80 Hz to 20 kHz
Low-distortion Class-D digital amplification
Adaptive noise reduction for maximising intelligibility
Multi-band dynamic-range compression prevents distortion and clipping at loud volumes

Microphones

Four cardioid super low-noise microphones
Noise transmission from table minimized (boundary mode)

Quad-planar beam forming isolates current talker and reduces noise

Pickup range of voice up to 5m (3m recommended)

Audio

Full-duplex, HD, wideband
Time and frequency domain acoustic echo cancellers
Adaptive noise suppression
Automatic environmental adaptation
Voice activity detection
Environmentally adaptive automatic gain control
Adaptive jitter buffers
Packet-loss concealment
48 kHz sampling rate
Super low latency audio processing
Illuminated capacitive-touch mute control

Network

Two 100/1000Mbps Ethernet ports provide inline connectivity between touchscreen controller and room system