

Pronto 210

Instant presentation sharing in any workspace

Pronto 210 transforms any area into a productive workspace where users can share in an instant, from any device.

Enterprises remain in control with built-in centralized management, monitoring, and reporting.

Always up-to-date and ready, Pronto 210 delivers a seamless experience for users and peace-of-mind for IT administrators.



Share in an instant

- The quickest way to share your screen to the room
- Connect directly to any Windows and macOS laptop with no need for adapters or other accessories
- StarLeaf users don't need to run additional software and can present immediately
- Visitors and guests can also share seamlessly and securely

Enterprise ready

- Secure connectivity with all data transmission encrypted
- Centralized management, monitoring, and reporting for IT administrators
- Automatic software updates ensure peace-of-mind with all systems always up-to-date and ready

Future-proof

- Future-proof performance designed for any space
- Exceptional 4K Ultra HD quality output
- Share from any device with support for wireless sharing via Miracast, Airplay, and Chromecast**

**coming soon



Pronto 210

TECHNICAL SPECIFICATIONS

Content output

1x HDMI 2.0 4K 3840x2160 @ 60fps

Content input

1x Pronto 4100, 1080p, 30fps

Support for additional Pronto 4100**

Airplay 1080p, 30fps**

Miracast 1080p, 30fps**

Chromecast 1080p, 30fps**

**coming soon

Dimensions

Pronto Hub 20

H 51mm (2.01"), W 115mm (4.53"), D 111mm (4.37")

Pronto 4100 connector

H 50mm (2.0"), W 42mm (1.7"), D 10mm (0.4")

Pronto 4100 cable

5m + 5m (16'4" + 16'4")

Box contents

Pronto Hub 20

Pronto 4100 cable (5m + 5m / 16'4" + 16'4")

Wall mounting bracket for Pronto Hub 20

Power supply with attachable UK, EU, US, AUZ adapters

Ethernet cable (2m / 6'6")

HDMI cable (3m / 9'9")

Weight

Pronto Hub 20

659g / 1.46 lbs

Pronto 4100

275g / 0.6lbs

Power supply

AC-DC converter with attachable UK, EU, US, AUZ adapters

Input: 100-240V AC, 1.5A, 50-60Hz

Output: 19V DC, 3.43A, 65W max.

Power consumption

10W typical, 30W max, 6.5W standby

Network

1x Gigabit Ethernet

802.11ac Wi-Fi IEEE 802.11a/b/g/n compatible

Temperature range

0°C - 50°C (32°F - 122°F)

Designed and manufactured in the UK

ABOUT STARLEAF

StarLeaf enables seamless collaboration through intelligently-engineered reliable meeting room systems, superior video conferencing and secure messaging.