

TSW-750

7" Surface Mount Touch Screen

- > Ultra clean, modern appearance
- > Thin profile and small footprint
- > Affordable and easy to install
- > 7" widescreen active-matrix color display
- > Core 3 UI™ graphics
- > 800 x 480 WVGA display resolution
- > Capacitive touch screen technology
- > High-performance H.264 streaming video
- > Rava™ SIP intercom and phone technology
- > WAV file customizable audio feedback
- > Built-in microphone and speakers
- > 5 soft-touch capacitive buttons
- > Single-wire Ethernet connectivity
- > PoE network powered
- > Standard electrical wall box mounting
- > Available in smooth black or white finish



CORE3UI™

Advanced Touch Screen Control

A Crestron® touch screen offers an ideal user-interface for controlling all the technology in your home, boardroom, classroom, courtroom, or command center. Touch screens do away with piles of remote controls, cluttered wall switches, and cryptic computer screens, simplifying and enhancing the way you use technology. For controlling home theater, multimedia presentation, audio, video, lighting, HVAC, and other systems, Crestron touch screens are fully-customizable with easy-to-use controls and icons, true feedback and real-time status display, full-motion video windows, and advanced navigation of digital media servers, tuners, and other devices.

With its clean, contemporary design highlighted by edge-to-edge glass and stunning Core 3 UI™ color graphics, the Crestron® TSW-750 touch screen makes an elegant statement on any wall or lectern. Perfectly at home in the most contemporary residence or modern office building, its high-tech good looks underline its power for simplifying everyday tasks and functions throughout any facility.

The TSW-750 delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7 inch capacitive touch screen display and 5 soft-touch buttons. PoE connectivity and standard gang-box mounting make installation a breeze for both new and retrofit applications. Additional features include high-performance H.264 video, Rava™ SIP Intercom, and advanced Core 3 UI touch screen graphics.

Powered by Core 3™

Crestron touch screens have always offered the ultimate user experience. With Core 3 UI, they also deliver the ultimate value, enabling the creation of dynamically rich user interfaces with incredible efficiency and unparalleled functionality. Using Core 3 UI, programmers can swiftly integrate fluid gesture-driven controls, animated feedback, metadata, embedded apps, and full-motion video for a deeply engaging and ultra-intuitive touch screen experience.

Some Core 3 UI enhancements:

- Cool-looking graphical buttons, sliders, knobs, and gauges are intuitive and fun to use.
- Kinetic effects enhance the feeling of realism with lists and toolbars that scroll with momentum at the flick of a fingertip.
- Drag-and-drop objects snap into place offering an easy way to assign assets to rooms.
- Desktop widgets personalize the touch screen with animated clocks, calendars, weather, news, and other information.
- Customizable themes allow a completely different look and feel for every user, event, or season.
- Fully-developed SmartObjects™ enable sophisticated control over complex devices with minimal programming.
- Smart resizing scales objects perfectly and instantly for faster GUI development — even across different sized touch screens.

Soft-Touch Buttons

The TSW-750 includes five soft-touch capacitive buttons for quick access to commonly used functions. The buttons are pre-labeled with icons for “Power”, “Home”, “Lights”, “Up”, and “Down” functions. Each button is programmable via the control system for custom functionality.

Streaming Video

High-performance streaming video capability makes it possible to view security cameras and other video sources over the network right on the touch screen. Native support for H.264 and MJPEG formats allows the TSW-750 to display live video images from Web cameras and servers such as the Crestron [CEN-NVS200 Network Video Streamer](#)^[1].

TSW-750 7" Surface Mount Touch Screen

Rava™ SIP Intercom

Rava SIP Intercom Technology enables hands-free VoIP communication between any two Rava-enabled Crestron touch screens. Rava works over Ethernet, supporting 2-way intercom, video intercom^[2], paging, and room monitoring without any special wiring. VoIP phone capability is also possible through integration with an SIP-compatible IP phone system or SIP server, allowing hands-free telephone functionality complete with speed-dialing, caller ID, custom ringers, and other enhancements. Built-in echo cancellation affords true-duplex performance for clear, seamless voice communication using the TSW-750's integrated microphone and speakers.

Audio Feedback

Customized WAV files can be loaded to add another dimension to the touch screen graphics using personalized sounds, button feedback, and voice prompts.

Single-Wire Connectivity

A simple Ethernet LAN connection is all that is required to wire the TSW-750, containing all control, video, intercom, and power signals within a single wire.

Power over Ethernet

Using 802.3af PoE technology, the TSW-750 gets its operating power right through the LAN wiring. PoE (Power over Ethernet) eliminates the need for a local power supply or any dedicated power wiring. A PoE Injector ([PWE-4803RU^{\[1\]}](#)) simply connects in line with the LAN cable at a convenient location. Crestron PoE switches ([CEN-SW-POE-5](#) or [CEN-SWPOE-24^{\[1\]}](#)) may also be used to provide a total networking solution with built-in PoE.

Simple, Versatile Mounting

The TSW-750 installs easily over a 2-gang or 3-gang electrical box, or a 2-gang European electrical box. It can also be attached directly to drywall and other surfaces over the front of a 2-3/8" H x 3-3/8" W (60mm H x 86mm W) cutout. When installed, it protrudes just 1/2 inch from the mounting surface and is magnetically adhered to its mounting bracket, eliminating any visible screws for an ultra clean appearance.

SPECIFICATIONS

Touch Screen Display

Display Type: TFT Active matrix color LCD
Size: 7 inch (178 mm) diagonal
Aspect Ratio: 15:9 WVGA
Resolution: 800 x 480 pixels
Brightness: 300 nits (cd/m²)
Contrast: 350:1
Color Depth: 18-bit, 262k colors
Illumination: Edgelit LED w/auto-brightness control
Viewing Angle: ±70° horizontal, ±65° vertical
Touch Screen: Projected Capacitive

Buttons

Hard Keys: (5) Projected capacitive pushbuttons, programmable, pre-labeled with icons for "Power", "Home", "Lights", "Up", and "Down"
Reset: (1) Miniature pushbutton on rear panel for hardware reset

Memory

DDR RAM: 1 GB
Flash: 4 GB
Maximum Project Size: 512 MB

Graphics Engine

Core 3 UI™, VT Pro-e® programmable

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, IEEE 802.3af compliant

Video

Streaming Formats: H.264 (MPEG-4 part 10 AVC), MJPEG

Audio

Features: Built-in microphone and speakers, Rava™ SIP Intercom
Audio Feedback Formats: WAV (8 & 16-bit PCM, mono & stereo, 8 – 44.1 kHz sampling rates), MP3 (variable bitrate)

Connectors

LAN PoE: (1) 8-wire RJ45 with 2 LED indicators;
10Base-T/100Base-TX Ethernet port;
802.3af Power over Ethernet compliant;
Green and yellow LEDs indicate Ethernet port status

Power Requirements

Power over Ethernet: IEEE 802.3af Class 3 PoE Powered Device

Environmental

Temperature: 32° to 112°F (0° to 45°C)
Humidity: 10% to 90% RH (non-condensing)
Heat Dissipation: 44 BTU/hr

Enclosure

Construction: Plastic, smooth black or white finish
Mounting: Surface mount over a 2 or 3-gang electrical box, 2-Gang European (DIN 49073) electrical box, or 2-3/8" H x 3-3/8" W (60mm H x 86mm W) cutout

Dimensions

Height: 4.74 in (121 mm)
Width: 7.59 in (193 mm)
Depth: 2.03 in (52 mm)

TSW-750 7" Surface Mount Touch Screen

Weight

14.1 oz (400 g)

MODELS & ACCESSORIES

Available Models

TSW-750-B-S: 7" Surface Mount Touch Screen, Black Smooth

TSW-750-W-S: 7" Surface Mount Touch Screen, White Smooth

Available Accessories

PWE-4803RU: PoE Injector

CEN-SW-POE-5: 5-Port PoE Switch

CEN-SWPOE-24: 24-Port Managed PoE Switch

CEN-NVS200: Network Video Streamer

SW-VMK-WIN: TouchPoint™ Virtual Mouse & Keyboard Software for Windows®

Notes:

1. Item(s) sold separately.
2. H.264 compatible IP camera required.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Core 3, Core 3 UI, Crestron, Rava, SmartObjects, TouchPoint, VT Pro-e and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Windows is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others.
©2012 Crestron Electronics, Inc.

TSW-750 7" Surface Mount Touch Screen

